

Epoxy dispersant

RD-9291

Features and advantages:

1, used for dispersion of epoxy system, has excellent wetting effect, good dispersion effect on titanium dioxide, red, blue and green of epoxy system, increase the brightness of color, reduce the grinding time of pigment, not easy to return to coarse.

2. Stable dispersion of epoxy pigment, suitable for preparation of pigment concentrate slurry.

3. Good solubility in resin can reduce viscosity and provide liquidity.

Product specifications:

appearance	Colorless to light yellow transparent liquid
Effective ingredients	60%
composition	Polyester modified special

Application scope:

Industrial coatings, canned coatings, epoxy coatings, etc

Recommended dosage:

Titanium dioxide	3-6%
Organic pigments	10-20%
Carbon black	30-50%
The whole amount	0.3-1.5%

Usage :

To achieve full effect, auxiliaries must be added to the abrasive before they are added to the pigment. The resin and solvent components of the abrasive are pre-mixed, and the additive is slowly added in a stirred state. Only when the additive is completely dispersed, can the pigment be added. Please test the appropriate amount before use.

Packing: 25KG non-recycled blue plastic drum. The product is not completely used, need to tighten the lid after use.

Storage: keep away from fire and light source and keep away from light

Note: please evaluate carefully before use, suitable for matte furniture paint, also can be applied to bright light.