

Defoamer

RP-6293

Features and advantages:

RP-6293 is used as a defoamer and defoaming agent for unsaturated polyester, epoxy and PVC systems. Rapid defoaming in thermosetting systems, also available for bubble-free self-leveling, polyurethane systems to speed up the defoaming process.

1. Used for unsaturated polyester, epoxy formula
2. Suitable for the formulation and varnish with pigment, excellent compatibility
3. High efficiency no solvent

Product specification:

Appearance	Yellowish transparent liquid
Solid content	100%
Make up	Non-silicone foaming polymer

Application field:

- Amine/amide cured epoxy coatings

Recommended addition

Total formula in the form of supply: 0.1-1.0%

- Varnish formula

Recommended addition

Total formula in the form of supply: 0.1-0.8%

- Unsaturated polyester paint

Recommended addition

Total formula in the form of supply: 0.1-1.0%

Technical Data Sheet

○ Polyurethane Coatings

Recommended addition

Total formula in the form of supply: 0.1-1.0%

○ Color paint formula

Recommended addition

Total formula in the form of supply: 0.1-0.8%

How to use:

Stir before use

Pre-diluted or added directly to the paint as supplied

Packing:

25kg, plastic drum; 200 kilos, iron drum

Storage:

Store unopened original packaging without freezing and use within 12 months.