

Defoamer

RP-6472

Characteristics and Benefits:

RP-6472 is a defoamer for solvent-based, non-solvent-based and radiation-cured coatings, particularly suitable for radiation-cured systems, two-component epoxy systems and clear coat formulations. It has high compatibility, good re-coatability, and excellent defoaming and breaking defoaming effects, making it suitable for thick coating and high viscosity systems.

1. For solvent-based, non-solvent-based and radiation-cured formulations
2. Suitable for clear coats, color paints and high viscosity system formulations
3. High compatibility, good re-coatability
4. Excellent defoaming and breaking defoaming effects, suitable for dip coating, roller coating

Product parameters:

Appearance	Light yellow transparent liquid
Valid copy	25%
Solvent	Butyl acetate
Chemical composition	Modified polymer (without silicone)

Application fields:

- Amine/amine-cured epoxy floor coatings

Recommended addition amount

As a percentage of the total formulation based on the supplied form: 0.1 - 1.0%

- Solvent-based and radiation-cured screen printing inks

Recommended addition amount

As a percentage of the total formulation based on the supplied form: 0.1 - 1.0%

- Radiation-cured varnish

Recommended addition amount

As a percentage of the total formulation based on the supplied form: 0.1 - 1.0%

Wood and furniture coatings

Recommended addition amount

As a percentage of the total formulation based on the supplied form: 0.1 - 0.8%

Automotive paint

Recommended addition

As a percentage of the total formulation based on the supplied form: 0.1 - 0.8%

Usage method:

1. Pre-dilution with the recommended solvent will facilitate addition and mixing.
2. Thorough stirring and mixing are necessary.

Packaging:

25 kilograms, plastic drum; 200 kilograms, iron drum

Storage:

Unopened original packaging should be stored at room temperature without freezing for up to 12 months.