



---

---

## Leveling agent

### RF-7490

#### Features and advantages:

Used in solvent-based and solvent-free (two component) formulations. Applicable to amine/amide cured epoxy floor coating leveling agent, anti-corrosion coating leveling agent, industrial coating leveling agent, wood and furniture coating leveling agent.

1. Used for solvent and volatile (two component) formulations
2. It has additional defoaming effect
3. Good recoating
4. Good fluidity improvement, varnish transparency, smooth, anti-shrinkage cavity effect and anti-adhesion/peeling effect

#### Product specifications:

appearance	Transparent liquid
Active substance content	100%
Chemical composition	Organosiloxane copolymer
viscosity, 25°C	about 300mPa . s

**Application scope:** Applicable to amine/amide cured epoxy floor coating leveling agent, anti-corrosion coating leveling agent,



---

---

industrial coating leveling agent, wood and furniture coating leveling agent.

**Recommended dosage:**

1. Amine/amide cured epoxy floor coatings

Recommended dosage: 0.05-1.0% for the total formula in the form of supply

2. Wood and furniture paint

Recommended dosage: in the form of supply for the total formula: 0.05-0.5%

3. Industrial coatings

Recommended dosage: 0.05-0.3% for the total formula in the form of supply

4. Anticorrosive paint

Recommended dosage: 0.05-0.3% for the total formula in the form of supply

**Usage:**

1. Pre-diluted or directly added to the coating in the form of supply

2. Pre-diluting with the recommended solvent will facilitate addition and mixing

**Packing:** 25KG plastic drum or 200KG iron drum

**Storage:** use within 12 months in unopened original packaging.